



WALLS

SENSIS TEXTURED

KERKSTOEL sensis textured walls



Description

The Sensis textured wall is a structural "twin" wall consisting of two reinforced concrete panels connected by lattice girders. Prefabricated wall elements are assembled on-site according to the plan and then filled with concrete. The result is a solid construction, as strong as an insitu cast concrete wall, with an unmistakable aesthetic flair.

Thicknesses

Thickness (outer-inner): 19 - 50 cm

Plate thickness: at least 5 cm (other dimensions upon request)

Dimensions

Length: up to 13.0 m

Height: up to 3.90 m

Tolerances in dimensions

In accordance with NBN-EN-14992 (Class B) and National Annex NBN-B21-612

Concrete compressive strengths

C30/37 - C50/60

Thermal

The Sensis textured wall is also available as a thermal variant with built-in insulation, allowing it to have excellent thermal properties in addition to structural and aesthetic ones.


Advantages

- Customisation: The wall is fully customised with the structure that perfectly fits your vision.
- No need for additional facade cladding or finishing: Save costs and shorten lead times.
- Quick installation: Significantly reduce installation time.
- Durability: Enjoy a durable facade, insulated or not.
- Adaptability: Choose from countless texture possibilities.

Options



WOOD



LINES

Available in
up to 100
different
textures!



ROUGH



BRICKS